



SPECIALTY SALES & SERVICE

1954 North Linn Avenue • New Hampton, Iowa 50659
 Ph: (641) 394-3141 • Fax (641) 394-3823 • www.mitkollc.com

Customer: New Hampton Community School

Number: 641-330-5978

710West Main, New Hampton Iowa

Quantity	Model	Description	Cash Price
1	CS2520	KTT-CS2520H-I KIOTI Tractor, 24.5 HP, MFWD, Industrial Tires	\$ 14,709.00
		Rear and Mid PTO, Joystick Valve, Cruise Control, Tilt Steering Wheel	\$ -
		Headlights, Warning and Signal Lights, 12v USB and Power Port	\$ -
		2 Year (1500hr) Bumper to Bumper Warranty	\$ -
		3 Year (2000hr) Powertrain Warranty	\$ -
			\$ -
1	SM2460	SM2460 60" Mid Mount Mower, Side Discharge, 3 Blade	\$ 2,069.00
		U Joint Shaft and V Belt Drive	\$ -
		1 Year Warranty	\$ -
			\$ -
			\$ -
			\$ -
			\$ -
			\$ -
		Subtotal	\$ 16,778.00
		Battery, Freight, and Set-up	\$ 1,575.00
		Subtotal	\$ 18,353.00
		Non Profit Municipal Discount	\$ (1,928.61)
			\$ -
		Mitko Dealership Discount	\$ (3,435.39)
		<i>Optional Equipment:</i>	
	CSA2420	KIOTI 2420 Loader 48" Quick Attach Bucket, 1062.3 lb. Lift Capacity, 1329 lb. Breakout Force, 6.7 cu. ft. Capacity	\$ 3,026.00
	AAA206	48" Bolt on Cutting Edge	\$ 158.00
		1 Year Warranty on Implements	
		Non Profit Municipal Discount	(-400)
		Mitko Dealership Discount	(-207)
		Optional Equipment Total:	\$ 2,577.00
		Price is only valid with current rebates and manufacturers current pricing.	
		Tax and Freight is not included in this purchase agreement.	
		Tractor/Mower Subtotal	\$ 12,989.00
		Est. Sales Tax (7%)	Exempt
		Down Payment Required	
		Balance at Delivery	\$ 12,989.00

Thank You

Purchaser's Signature

Date

Dealer or Authorized Representative

SPECIFICATIONS

MODEL		CS2210	CS2220	CS2510	CS2520	
ENGINE						
Model		3C100LWH-U3	3C100LWH-U3	3C100LFH-U2	3C100LFH-U2	
Type		Liquid Cooled 3 Cyl., Diesel				
Engine Gross	hp (kW)	21 (15.6)	21 (15.6)	24.5 (18.3)	24.5 (18.3)	
PTO @ Rated PTO rpm	hp (kW)	16.3(12.2)	16.3(12.2)	18.5(13.9)	18.5(13.9)	
Displacement	cu. in. (cc)	61.5(1,007)	61.5(1,007)	61.5(1,007)	61.5(1,007)	
Rated Revolution	rpm	3,200	3,200	3,200	3,200	
Fuel Tank Capacity	US. gal. (ℓ)	6.7 (25.5)				
DRIVE TRAIN						
Transmission		HST				
Speeds		Infinite, 2 range				
Differential Lock		Rear Standard				
Brake		Wet Multi Disc				
PTO Type		Independent				
Rear PTO (Standard)	rpm	540				
Mid PTO (Standard)	rpm	2,200				
4WD Type		Mechanical Engagement				
HYDRAULIC SYSTEM						
Pump		Gear				
Pump Capacity (Max. Flow Rate)	gpm (L/min)	6.5 (24.6)	6.97 (26.4)	6.5 (24.6)	6.97 (26.4)	
3-Point Hitch		Category I				
Maximum Lifting Capacity (24" aft. of hitch)	lb. (kg)	700 (318)				
Hydraulic Lift Control System		Position				
Steering		Power Steering				
TIRE SIZE						
Front AG. (Turf, Industrial)		18×8.5-10 (18×8.5-10)				
Rear AG. (Turf, Industrial)		26×12.00-12 (26×12.00-12)				
TRAVELING SPEEDS						
Forward	mph (km/h)	0~10.31(0~16.6)	0~9.57 (0~15.4)	0~10.31(0~16.6)	0~9.57 (0~15.4)	
Reverse	mph (km/h)	0~6.96 (0~11.2)	0~6.6 (0~10.6)	0~6.96 (0~11.2)	0~6.6 (0~10.6)	
DIMENSIONS						
Overall Length (Includes 3-pt Hitch)	in. (mm)	99.3 (2,523)				
Overall Width (Minimum Tread)	in. (mm)	46.7 (1,185)	45.9 (1,168)	46.7 (1,185)	45.9 (1,168)	
Overall Height (From Top of ROPS)	in. (mm)	88 (2,226)				
Wheelbase	in. (mm)	55.1 (1,400)				
Min. Ground Clearance	in. (mm)	6.4 (162)				
Tread	Front (AG.)	in. (mm)	45.3 (1,150)	45.9 (1,168)	45.3 (1,150)	45.9 (1,168)
	Rear (AG.)	in. (mm)	46.7 (1,185)	46 (1,168)	46.7 (1,185)	46 (1,168)
Min. Turning Radius (With Brake)	ft. (m)	8.2 (2.54)				
Weight with AG. Tires	lb. (kg)	1,485 (675)	1,554 (705)	1,485 (675)	1,554 (705)	

* NOTE : Specifications and design are subject to change without notice.



ISO 9001
NO.954596



ISO 14001
NO.771475



OHSAS 18001
NO:K033008

STANDARD EQUIPMENT

- Rear PTO
 - Mid PTO
 - Joystick Valve (CS20 Series)
 - Cruise Control (CS20 Series)
 - 12V/USB Port (CS20 Series)
 - 12V Power Socket (CS10 Series)
 - Tilt Wheel (CS20 Series)
 - Grill Guard¹
 - Power Steering
 - Parking Brake
 - PTO Shield
 - Headlights
 - Warning / Signal Lamps
 - Cup Holder
 - Horn
 - SMV Sign
- ¹When loader is purchased with tractor.

OPTIONAL EQUIPMENT

- Front Hydraulic Valve (CS10 Series)
- Rear Hydraulic Valve
- Front Working Lights (CS20 Series)
- Rear Working Lights
- Cruise Control (CS10 Series)
- Front Weight (60 lbs)
- Side View Mirror
- Canopy Kit
- Grill Guard
- Armrest Kit
- Front Towing Hook
- Hydraulic Filter Guard
- Rear Wheel Weight
- Field Option Cab (CS10 Series)

ATTACHMENTS

- Front End Loader
- Mid-Mount Mower
- Backhoe
- Snow Blower
- Contact your local KIOTI dealer for available implements and attachments.



KIOTI Tractor Division

DAEDONG - USA, INC.
6300 KIOTI Drive, Wendell, NC 27591 USA
Toll free 877-60-KIOTI • Fax 919-374-5001
Web www.KIOTI.com



Mitko LLC
1954 N Linn Ave
New Hampton IA 50659
Phone: 641-394-3141
Website: www.mitkollc.com



Mid-Mount Mower

MODEL	SM2410	SM2454	SM2460
Compatible Models	CS10 Series	CS10 / CS20 Series	CS10 / CS20 Series
Discharge Type	Side Discharge	Side Discharge	Side Discharge
Cutting Width	60 in. (1,524 mm)	54 in. (1,364 mm)	60 in. (1,524 mm)
Cutting Height	1-4 in. (25.4-101.6 mm)	.8-3.8 in. (20.3-96.5 mm)	.8-3.8 in. (20.3-96.5 mm)
Transport Height	6 in. (152.4 mm)	6 in. (152.4 mm)	6 in. (152.4 mm)
Gear Type	Spiral Bevel	Spiral Bevel	Spiral Bevel
Number of Blades	3	3	3
Blade Spindle Speed	2,888 rpm	2,888 rpm	2,888 rpm
Blade Tip Velocity	78.2 m/s	71.1 m/s	78.2 m/s
Blade Length	20.4 in. (517 mm)	18.5 in. (470 mm)	20.4 in. (517 mm)
Deck Thickness	0.13 in. (3.2 mm)	0.13 in. (3.2 mm)	0.13 in. (3.2 mm)
Total Width	73.4 in. (1,865 mm)	69.3 in. (1,760 mm)	75 in. (1,905 mm)
Total Length	37.9 in. (962 mm)	35.7 in. (908 mm)	37.9 in. (962 mm)
Total Height	10.8 in. (273 mm)	10.5 in. (267 mm)	10.8 in. (273 mm)
Drive Type	U-Joint and V-Belt	U-Joint and V-Belt	U-Joint and V-Belt
Lifting Type	3 Point Hitch Links	3 Point Hitch Links	3 Point Hitch Links
Loader / Backhoe Compatibility	Yes	Yes	Yes

Front End Loader

MODEL	SL2410	SL2420
Compatible Models	CS2210 / 2410 / 2510	CS2220 / 2520
Maximum Lift Height (to Pivot Pin)	71.3 in. (1,810 mm)	73.7 in. (1,872 mm)
Clearance w/ Bucket Level	64.5 in. (1,638 mm)	68.1 in. (1,730 mm)
Clearance w/ Bucket Dumped	51 in. (1,298 mm)	54.8 in. (1,392 mm)
Reach at Maximum Height	26.7 in. (678 mm)	29.7 in. (755 mm)
Maximum Dump Angle	45°	38°
Reach w/ Bucket on Ground	52.4 in. (1,332 mm)	52.8 in. (1,342 mm)
Maximum Rollback Angle	27°	27°
Digging Depth Below Grade	5.1 in. (130 mm)	5.1 in. (130 mm)
Overall Height (in Carry Position)	36.4 in. (925 mm)	34.1 in. (867 mm)
Depth of Bucket (to back of inner shell)	19.9 in. (507 mm)	18 in. (457.3 mm)
Height of Bucket	18.1 in. (459 mm)	19 in. (484 mm)
Length of Bucket (to pivot pin)	23.1 in. (588 mm)	22.4" (569.4 mm)
Lift Capacity to Full Height (at Pivot Pins)	675.3 lbs. (306.3 kg)	1062.3 lbs. (482 kg)
Breakout Force (at Pivot Pins)	1,332 lbs. (604 kg)	1,329 lbs. (603 kg)
Bucket Rollback Force (at Ground Line)	1,109 lbs. (503 kg)	904 lbs. (410 kg)
Relief Valve Setting (Loader Control Valve)	1,900 psi (133.6 kg/cm2)	1,900 psi (133.6 kg/cm2)
Rated Flow (Tractor System)	3.5 gpm (13.4 L/min)	4.9 gpm (18.7 L/min)
Bucket Size (QA)	48 in.	48 in.
Bucket Capacity (Heaped)	6.7 cu. ft.	6.7 cu. ft.
Approximate Weight (With Bucket)	498 lbs. (226 kg)	573 lbs. (260 kg)

Backhoe

MODEL	SB2410L	SB2420
Compatible Models	CS2210 / 2410 / 2510	CS2220 / 2520
Bucket Sizes	8 in. 12 in. 16 in.	8 in. 12 in. 16 in. 24 in.
Digging Depth (Two Foot Flat Bottom)	72.8 in. (1,850 mm)	72.8 in. (1,850 mm)
Reach from Center Line of Swing Pivot	105.7 in. (2,684 mm)	105.7 in. (2,684 mm)
Loading Height (Bucket at 60°)	59.1 in. (1,500 mm)	59.1 in. (1,500 mm)
Maximum Leveling Angle	8°	8°
Swing Arc	150°	150°
Transport Height (Maxim um)	68.1 in. (1,729 mm)	68.1 in. (1,729 mm)
Transport Overhang	41.3 in. (1,050 mm)	41.3 in. (1,050 mm)
Bucket Rotation	165°	165°
Stabilizer Spread (Down Position)	78 in. (1,981 mm)	78 in. (1,981 mm)
Stabilizer Spread (Up Position)	54 in. (1,372 mm)	54 in. (1,372 mm)
Angle of Departure	14.5°	20°
Shipping Weight (Without Bucket)	635 lbs. (288 Kg)	635 lbs. (288 Kg)
Bucket Digging Force	2,105 lbs. (955 Kg)	2,105 lbs. (955 Kg)
Dipperstick Digging Force	1,183 lbs. (537 Kg)	1,183 lbs. (537 Kg)
Operating Pressure	1,885 psi. (130 bar)	1,885 psi. (130 bar)

* Specifications and design are subject to change without notice.

