



MASSEY FERGUSON

Prepared for:	New Hampton Community Schools
Good Through:	03-31-2022
Dealer Representative:	steven Kincannon
Representative Email:	steven.kincannon@zieglercat.com
Representative Phone:	

Cash Price

Model #	MSRP
MFGC1725M Compact Tractor	\$ 15,585.00
Multi-unit quote attachments: 1) MF2326 Mower	
Total Prep and Delivery	\$ 777.00
Total Retail Price	\$ 16,362.00

	Cash Price	
<u>e</u>	Sale Price	\$ 13,887.00
ž	Trade-In:	\$ 0.00
5	Net Price	\$ 13,887.00
u S S	Taxes	\$ 0.00
	Final Customer Price	\$ 13,887.00



\$13,887.00







This Letter is a non-binding indication of interest regarding a possible transaction on the general terms and conditions outlined herein and is not a legal commitment. This Letter is intended for the use of the Customer only. *The following is a proposal for financing for the customer named herein ("Customer") regarding the equipment described herein ("Equipment") by AGCO Finance LLC for discussion purposes only. Customer participation subject to credit qualification and approval by AGCO Finance LLC. Not all Customers may qualify for this rate or term. This proposal is not a statement of all terms and conditions of any financing that may be approved. This Letter is intended for the use of the Customer only. This Letter is valid until "Good Through" date listed above and thereafter shall automatically be deemed to be null and void. ***The cash price is a good faith dealer estimate only. See dealer for details.



Model Number: Model Year: 2022

MFGC1725M

QQ Number: QQ-0617727 Serial Number:

Invoice Number: Order Number:

Dealership Name: Ziegler Ag Equipment Location: New Hampton (632642)





MASSEY FERGUSON

Line Item details of components on MFGC1725M Compact Tractor

- MFGC1725M Compact Tractor
- GC1725M HST Platform
- F18X8.50-10 R26X12.00-12 TUR
- NA Assembly Package
- EN Operator's Manual GC170
- Proposition 65 Decal

Line Item details for Attachment #1 - MF2326 Mower

MF2326 60" Drive-Over

Mower

Prepared for: New Hampton Community Schools Good Through: 03-31-2022 Dealer Representative: steven Kincannon Representative Email: steven.kincannon@zieglercat.com Representative Phone:



GC1725M GARDEN COMPACT

(F.O.B. Port of Entry)

TRACTOR FEATURES

POWER TRAIN

- Engine:
 - 24.5 Gross HP 3 Cyl Diesel
 - 1.12 L Displacement
 - 23.6 Net HP @ 3000 RPM
- 18.5 PTO HP @ 3000 RPM • Dry Type Single Air Cleaner
- Dry Type Single Air Cleaner
 Transmission: 2 Range Hydrostatic with
- Cruise Control
- Wet Disk Brakes
- Parking Brake
- Differential Lock
- PTO: 540 RPM Independent PTO 2000 RPM Mid Independent PTO

HYDRAULIC SYSTEM

- 3-Point Hitch, Cat I With Directional Control, Auto Return Lever System
- · Engine Driven Gear Pump
- 3-Point Hitch 4.9 GPM (18.8 LPM)
- Power Steering 2.0 GPM (7.5 LPM)
- Total Combined Flow 6.9 GPM (26.3 LPM)

INSTRUMENTS

- Tachometer / Hourmeter
- Engine Coolant Gauge Fuel Gauge
- Warning Lights: Electrical Charging and Oil Pressure and Water Temperature

OTHER STANDARD FEATURES

- · Hydrostatic Power Steering
- Tilt Steering Column
- Hand Accelerator
- · Forward And Reverse Foot Pedal
- · Rubber Floor Mat
- Covered Storage Compartment with 12V Socket
- Electric Fuel Shut-Off
- 12 Volt Electrical System
- Battery: 390 Cold Cranking Amps
- Fully Adjustable Swivel Seat with Armrests and Retractable Seatbelt
- 2 Post Fixed ROPS
- Tilt-Up Hood
- Turn Signals, Flashers, Tail Lights
- Factory Joystick
- Hydraulic Manifold with Pressure and Return Lines on Model with Factory Joystick
- Note: 3-Point Mounted Backhoe Installation Voids Warranty. Use the Required Subframe Mounting Kit.

IMPLEMENT FEATURES

MF FL1805 LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 1.57 inch Double Acting Lift Cylinders
- (2) 1.57 inch Double Acting Bucket Cylinders
- Simultaneous Operation of Lift/Lower and Curl/Dump Functions
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Pins with Recessed Grease Points
- 48-inch Standard Duty Skid Steer Bucket
- Grille Guard Standard
- Maximum Lift Height at Pivot Pins: 74 Inches
- · Lift Capacity to Full Height at Pivot Pins: 922 lbs
- Breakout Force at Pivot Pins: 1,392 lbs
- Rated Hydraulic Pressure: 1,920 PSI
- Fits all GC1700 Series Tractors

AVAILABLE ATTACHMENTS (REFER TO IMPLEMENT SECTIONS)

- · MF 2315, 2320 and 2326 Mid Mounted Mowers
- MF 2360 Front Mounted Snow Blower
- MF 2330 Front Mounted Rotary Broom
- MF 2335 Front Mounted Blade
- MF 2340 Front Mounted Heavy Duty Blade

March 2022

MF2300 SERIES MOWER



(F.O.B. Port of Entry)

FEATURES

- Mid-Mounted Stamped Tunnel Deck •
- Right Hand Discharge (only on MF2320 and 2326) •
- Mulching Deck (Only 2315) .
- .
- Cutting Width: MF2315: 54 inches MF2320: 54 inches MF2326: 60 inches
- Six (6) Overlapping Offset Mulching Blades on MF2315 Three (3) Overlapping Offset Blades on MF2320 and MF2326
- · Cutting Height:
 - MF2315: 1.3 4.9 inches MF2320: 1.2 4.7 inches MF2326: 1.2 4.7 inches
- · Lift: Parallel Linkage, Hydraulic
- Transport Height: 5.9 inches
- · Lock-up Kit Standard. Allows use of 3-Point

- · Quick Disconnect with Single Handle Front Latch and Two Spring Loaded Pins at Rear
- Compatible with Loader and Backhoe .
- Mid PTO Driveshaft to Mower Gear Box
- Blade Tip Speed: MF2315: 16,200 FPM MF2320: 17,200 FPM • MF2326: 17,600 FPM
- Two (2) Front Hard Rubber Gauge Wheels with Bearings, Castering Regreasable
- Two (2) Rear Hard Rubber Gauge Wheels with Bearings, Regreasable
- One (1) Front Roller and Two (2) Rear Rollers
- Note! Backhoe must be removed on TLB versions in ٠ order to install mower

QQ-0617727