



**Project:**  
New Hampton HS - Camshelving

**From:**  
Wilson Restaurant Supply  
Tyler Zook  
5746 Westminster Dr.  
Cedar Falls, IA 50613-  
(319)277-9000  
(319)277-9000 (Contact)  
(319)240-7512  
(319)277-9007 (Fax)  
wilsonrscf@gmail.com

Job Reference Number: 6453

Item	Qty	Description	Sell	Sell Total
Walk-In Freezer	1 ea	<b>SHELVING UNIT, PLASTIC WITH POLY EXTERIOR STEEL POSTS</b>	463.32	463.32
		Cambro Model No. CPU244872V4480 Camshelving® Premium Starter Unit, 24"W x 48"L x 72"H, 4-tier, withstands temperature -36°F (-38°C) to 190°F (88°C), includes: (4) vented polypropylene shelf plates with Camguard™ antimicrobial protection, (2) pre-assembled post kits (posts constructed of steel with polypropylene exterior), (8) traverses & molded-in dovetails, 800 lbs. capacity per shelf /2,000 lbs. max capacity, speckled gray, NSF		
	2 ea	CPA244272V4480 Camshelving® Premium Add-On Unit, 24"W x 42"L x 72"H, 4-tier, withstands temperature from -36°F (-38°C) to 190°F (88°C), includes: (4) vented polypropylene shelf plates with Camguard™ antimicrobial protection, (1) pre-assembled post kit (posts constructed of steel with polypropylene exterior), (8) traverses & molded-in dovetails, 800 lbs. capacity per shelf /2,000 lbs. max capacity, speckled gray, NSF (ships in 2 cartons)	365.04	730.08
	7 ea	CPA244872V4480 Camshelving® Premium Add-On Unit, 24"W x 48"L x 72"H, 4-tier, withstands temperature from -36°F (-38°C) to 190°F (88°C), includes: (4) vented polypropylene shelf plates with Camguard™ antimicrobial protection, (1) pre-assembled post kit (posts constructed of steel with polypropylene exterior), (8) traverses & molded-in dovetails, 800 lbs. capacity per shelf /2,000 lbs. max capacity, speckled gray, NSF (ships in 2 cartons)	393.12	2,751.84
	2 ea	CPA245472V4480 Camshelving® Premium Add-On Unit, 24"W x 54"L x 72"H, 4-tier, withstands temperature from -36°F (-38°C) to 190°F (88°C), includes: (4) vented polypropylene shelf plates with Camguard™ antimicrobial protection, (1) pre-assembled post kit (posts constructed of steel with polypropylene exterior), (8) traverses &	432.90	865.80

Item	Qty	Description	Sell	Sell Total
		molded-in dovetails, 800 lbs. capacity per shelf /2,000 lbs. max capacity, speckled gray, NSF (ships in 2 cartons)		
	1 st	CPCC10480 Camshelving® Premium Corner Connector Set, left & right, speckled gray (10 sets)	31.22	31.22
	2 st	CPCC1480 Camshelving® Premium Corner Connector Set, left & right, speckled gray (1 set)	3.14	6.28
	3 ea	CPDS24H6480 Camshelving® Premium Dunnage Support, 24"D x 7-1/2"H, low, recommended for units 54" or longer with weight loads over 600 lbs., speckled gray, NSF	44.72	134.16
Cooler and Dry Storage	1 ea	<b>CAN RACK</b>	465.66	465.66
		 Cambro Model No. CPA243672C96480 Camshelving® Premium Ultimate #10 Can Rack Stationary Add-On Unit, 24"W x 36"L x 72"H (26"W with can rack overhang) , includes: (1) assembled post kits (posts constructed of steel with polypropylene exterior), (9) traverses & molded-in dovetails, (15) can rack panels, (72) can rack brackets, 800 lbs. capacity per shelf /2,000 lbs. max capacity, speckled gray (assembly required)		
	1 ea	CPU243672C96480 Camshelving® Premium Ultimate #10 Can Rack Stationary Unit, 24"W x 36"L x 72"H (26"W with can rack overhang), includes: (2) assembled post kits (posts constructed of steel with polypropylene exterior), (9) traverses & molded-in dovetails, (15) can rack panels, (72) can rack brackets, 800 lbs. capacity per shelf /2,000 lbs. max capacity, speckled gray (assembly required)	549.90	549.90
	2 kt	CPPK1472480 Camshelving® Premium Post Kit, 14"W x 72"H, includes: (2) posts & (1) set of post connectors (top & bottom), 2 post kits are required for one Camshelving unit & 1 for add-on unit, speckled gray, NSF	63.18	126.36
	2 kt	CPMPK2467480 Camshelving® Post Kit, for mobile unit, 24"W x 67"H, includes: (2) premium swivel casters with total locking brake, (2) posts & (1) set of post connectors (top & bottom), speckled gray, NSF	149.76	299.52
	4 kt	CPSK1442V1480 Camshelving® Premium Shelf Plate Kit, 14"W x 42"L, withstands temperature from -36°F (-38°C) to 190°F (88°C), includes: (1) vented reinforced polypropylene shelf plate with Camguard™ antimicrobial protection & (2) traverses, speckled gray, NSF listed components	61.31	245.24
	3 kt	CPSK2436S1480 Camshelving® Premium Shelf Plate Kit, 24"W x 36"L, withstands temperature from -36°F (-38°C) to 190°F (88°C), includes: (1) solid reinforced polypropylene shelf plate with Camguard™ antimicrobial protection & (2) traverses, speckled gray, NSF listed components	68.33	204.99
	2 ea	CPU244272V4480 Camshelving® Premium Starter Unit, 24"W x 42"L x	432.90	865.80

Item	Qty	Description	Sell	Sell Total
		72"H, 4-tier, withstands temperature -36°F (-38°C) to 190°F (88°C), includes: (4) vented polypropylene shelf plates with Camguard™ antimicrobial protection, (2) pre-assembled post kits (posts constructed of steel with polypropylene exterior), (8) traverses & molded-in dovetails, 800 lbs. capacity per shelf /2,000 lbs. max capacity, speckled gray, NSF		
2 ea		CPA243672V4480 Camshelving® Premium Add-On Unit, 24"W x 36"L x 72"H, 4-tier, withstands temperature from -36°F (-38°C) to 190°F (88°C), includes: (4) vented polypropylene shelf plates with Camguard™ antimicrobial protection, (1) pre-assembled post kit (posts constructed of steel with polypropylene exterior), (8) traverses & molded-in dovetails, 800 lbs. capacity per shelf /2,000 lbs. max capacity, speckled gray, NSF (ships in 2 cartons)	325.26	650.52
4 ea		CPA244272V4480 Camshelving® Premium Add-On Unit, 24"W x 42"L x 72"H, 4-tier, withstands temperature from -36°F (-38°C) to 190°F (88°C), includes: (4) vented polypropylene shelf plates with Camguard™ antimicrobial protection, (1) pre-assembled post kit (posts constructed of steel with polypropylene exterior), (8) traverses & molded-in dovetails, 800 lbs. capacity per shelf /2,000 lbs. max capacity, speckled gray, NSF (ships in 2 cartons)	365.04	1,460.16
1 st		CPCC8480 Camshelving® Premium Corner Connector Set, left & right, speckled gray (8 sets)	24.94	24.94
1 ea		CPDS24H6480 Camshelving® Premium Dunnage Support, 24"D x 7-1/2"H, low, recommended for units 54" or longer with weight loads over 600 lbs., speckled gray, NSF	44.72	44.72
			Subtotal	9,920.51
			Total	9,920.51